

USB 2.0 A female to B female Panel Mount Cable



Description:

Farsince High Quality USB 2.0 A Female to B Female Panel Mount Cable is the perfect solution for combining USB Type-A and USB Type-B cables to achieve connectivity through a panel. This allows the user to provide connectivity from a source that is contained within a secure location. USB 2.0 A to B Panel Mount Cable cable is short and designed for minimal signal loss.

It provides a transfer rate up to 480Mbps depending upon the peripheral's USB version, and easily attaches to any USB device. Flexible PVC jacket, Foil and braid shielding, and the twisted pair construction make a better performance.

Item no. FSP1040

Specification:

- Connector 1: USB 2.0 Type-A female with screw locking
- Connector 2: USB 2.0 Type-B female with screw locking
- Gold plated contact, Nickel plated shell
- Nut and Screw type: M3 nickel plated
- Hole Pitch: 30 ± 0.5 mm
- Cable Conductor: Bare Copper
- Wire Gauge: 28/24AWG
- Outer diameter: 4.5 ± 0.2 mm
- Shielding: Aluminum foil, Braiding
- Housing: Injection molding
- Jacket: PVC
- Support high speed USB 2.0 devices and the transfer rate reaches to 480Mbps
- Backward compliant with full-speed USB 1.1 (12 Mbps) and low speed USB 1.0 (1.5 Mbps)
- Compliance: RoHS, REACH

Order Informaiton:

- FSP1040: USB 2.0 A female to B female Panel Mount Cable, 0.3m, 28AWG, OD 4.5 ± 0.2 mm