

## USB 3.0 A female to female Panel Mount Cable



### Description:

The USB 3.0 panel mount cable is designed to deliver connectivity from a secure location source. Its short, meticulous design is crafted for minimal signal loss.

Plus, it delivers a swift transfer rate of up to 4.8 Gbps, contingent upon the peripheral's USB version, and it affixes effortlessly to any USB device.

Equipped with foil and braid shielding, this cable completely combats EMI/RFI interference, while its twisted pair construction minimizes crosstalk, promising high-speed, error-free data transfer.

**Item no. FSP1060**

### Specification:

- Connector 1: USB 3.0 A female
- Connector 2: USB 3.0 A female with screw locking
- Gold plated contact, Nickel plated shell
- Nut and Screw type: M3 nickel plated
- Hole Pitch:  $30 \pm 0.5$ mm
- Cable Conductor: Bare Copper
- Wire Gauge: 28/28/24AWG
- Outer diameter:  $5.5 \pm 0.15$ mm
- Shielding: Aluminum foil, Braiding
- Housing: Injection molding
- Jacket: PVC
- Support high speed USB 3.0 devices and the transfer rate reaches to 4.8 Gbps
- Backward compliant with high-speed USB 2.0 (480Mbps), full-speed USB 1.1 (12 Mbps) and low speed USB 1.0 (1.5 Mbps)
- Compliance: RoHS, REACH

### Order Informaiton:

- FSP1060: USB 3.0 A female to female Panel Mount Cable, 0.3m, 28AWG, OD $5.5 \pm 0.15$ mm