

20PIN MotherBoard to Dual USB 3.0 A Female to Female Panel Mount Cable



Description:

Farsince High Quality 20PIN MotherBoard to Dual USB 3.0 A Female to Female Panel Mount Cable is the perfect solution for combining 20PIN MotherBoard and two USB Type-A cables to achieve connectivity through a panel. This allows the user to provide connectivity from a source that is contained within a secure location. The cable is short and designed for minimal signal loss. It provides a transfer rate up to 5Gbps depending upon the peripheral's USB version, and easily attaches to any USB device. Flexible PVC jacket, Foil and braid shielding, and the twisted pair construction make a better performance.

Item no. FSP1068

Specification:

- Connector 1: 20PIN MotherBoard female
- Connector 2: Dual USB 3.0 Type-A female with screw locking
- Gold plated contact, Nickel plated shell
- Nut and Screw type: M3 nickel plated
- Hole Pitch: 47 ± 0.5 mm
- Cable Conductor: Bare Copper
- Wire Gauge: 28/28/24AWG
- Outer Diameter: 5.5 ± 0.15 mm
- Shielding: Aluminum foil, Braiding
- Housing: Injection molding
- Jacket: PVC
- Support super speed USB 3.0 devices and the transfer rate reaches to 5 Gbps
- Backward compliant with high-speed USB 2.0 (480Mbps), full-speed USB 1.1 (12 Mbps), and low speed USB 1.0 (1.5 Mbps)
- Compliance: RoHS, REACH

Order Informaiton:

- FSP1068: 20PIN MotherBoard to Dual USB 3.0 A female Panel Mount Cable, 0.3m, 28AWG, OD 5.5 ± 0.15 mm