

USB 3.0 A female to B female Panel Mount Cable



Description:

Our prime asset facilitates the effortless unification of two USB cables through a panel, fostering secure connectivity from an encapsulated source.

Thoughtfully designed for minimal signal loss, it delivers a stunning transfer rate of up to 5 Gbps, dictated by the peripheral's USB version. Its easy-to-attach feature also facilitates swift connections with any USB device.

Boasting a resilient PVC jacket, this USB 3.0 A to B cable includes a foil and braid shielding for absolute immunity against EMI/RFI interference, with twisted pair construction reducing crosstalk for high-speed, error-free transfers.

Item no. FSP1077

Specification:

- Connector 1: USB 3.0 A female with screw locking
- Connector 2: USB 3.0 B female with screw locking
- Gold plated contact, Nickel plated shell
- Nut and Screw type: M3 nickel plated
- Hole Pitch: 30 ± 0.5 mm
- Cable Conductor: Bare Copper
- Wire Gauge: 28/28/24AWG
- Outer Diameter: 5.5 ± 0.15 mm
- Shielding: Aluminum foil, Braiding
- Housing: Injection molding
- Jacket: PVC
- Support super speed USB 3.0 devices and the transfer rate reaches to 5 Gbps
- Backward compliant with high-speed USB 2.0 (480Mbps), full-speed USB 1.1 (12 Mbps), and low speed USB 1.0 (1.5 Mbps)
- Compliance: RoHS, REACH

Order Information:

- FSP1077: USB 3.0 A female to B female Panel Mount Cable, 0.3m, 28AWG, OD 5.5 ± 0.15 mm