

## Panel Mount Micro USB 3.0 male to USB A male Cable with screw



### Description:

FARSINCE High Quality Micro USB 3.0 Male to A Male Panel Mount Cable is the perfect solution for combining Micro USB and USB Type-A cables to achieve connectivity through a panel. This allows the user to provide connectivity from a source that is contained within a secure location. Panel Mount Micro USB 3.0 male to USB A male Cable is short and designed for minimal signal loss.

It provides a transfer rate up to 5 Gbps depending upon the peripheral's USB version, and easily attaches to any USB device. Flexible PVC jacket, Foil and braid shielding, and the twisted pair construction make a better performance.

**Item no. FSP1085**

### Specification:

- Connector 1: Micro USB 3.0 male with screw locking
- Connector 2: USB 3.0 A male
- Gold plated contact, Nickel plated shell
- Nut and Screw type: M2 nickel plated
- Hole Pitch:  $19 \pm 0.5$ mm
- Cable Conductor: Bare Copper
- Wire Gauge: 28/28/24AWG
- Outer Diameter:  $5.5 \pm 0.15$ mm
- Shielding: Aluminum foil, Braiding
- Housing: Injection molding
- Jacket: PVC
- Support super speed USB 3.0 devices and the transfer rate reaches to 5 Gbps
- Backward compliant with high-speed USB 2.0 (480Mbps), full-speed USB 1.1 (12 Mbps) and low speed USB 1.0 (1.5 Mbps)
- Compliance: RoHS, REACH

### Order Information:

- FSP1085-005: 0.5m, 28/28/24AWG, OD $5.5 \pm 0.15$ mm
- FSP1085-010: 1.0m, 28/28/24AWG, OD $5.5 \pm 0.15$ mm
- FSP1085-018: 1.8m, 28/28/24AWG, OD $5.5 \pm 0.15$ mm
- FSP1085-030: 3.0m, 28/28/24AWG, OD $5.5 \pm 0.15$ mm