

Panel Mount Up Down Angle Micro USB 3.0 Male to USB A Male Cable with screw



Item no. FSP1086

Specification:

- Connector 1: Angle Micro USB 3.0 male with screw locking
- Connector 2: USB 3.0 A male
- Gold plated contact, Nickel plated shell
- Nut and Screw type: M2 nickel plated
- Hole Pitch: 19 ± 0.5 mm
- Cable Conductor: Bare Copper
- Wire Gauge: 28/28/24AWG
- Outer Diameter: 5.5 ± 0.15 mm
- Shielding: Aluminum foil, Braiding
- Housing: Injection molding
- Jacket: PVC
- Support super speed USB 3.0 devices and the transfer rate reaches to 5 Gbps
- Backward compliant with high-speed USB 2.0 (480Mbps), full-speed USB 1.1 (12 Mbps) and low speed USB 1.0 (1.5 Mbps)
- Compliance: RoHS, REACH



Description:

FARSINCE High Quality Angle Micro USB 3.0 Male to A Male Panel Mount Cable is the perfect solution for combining Micro USB and USB Type-A cables to achieve connectivity through a panel. This allows the user to provide connectivity from a source that is contained within a secure location. Panel Mount Up Down Angle Micro USB 3.0 Male to USB A Male Cable is short and designed for minimal signal loss.

It provides a transfer rate up to 5 Gbps depending upon the peripheral's USB version, and easily attaches to any USB device. Flexible PVC jacket, Foil and braid shielding, and the twisted pair construction make a better performance. The angled design provides the possibility for connection in small spaces.

Order Information:

U: Up Angle, D: Down Angle

- FSP1086U: 1.5m, 28/28/24AWG, OD 5.5 ± 0.15 mm, Up Angle
- FSP1086D: 1.5m, 28/28/24AWG, OD 5.5 ± 0.15 mm, Down Angle