

USB 3.1 Type C female to female Panel Mount Cable



Description:

Merging two USB Type C cables to facilitate panel connectivity has never been simpler.

This setup enables secure source location connectivity for you. And its short length and deliberate design contribute to its minimal signal loss. With a transfer rate of up to 10 Gbps, the USB C panel mount extension cable can easily connect to any USB device.

Equipped with foil and braid shielding, it offers total protection against EMI/RFI interference, while its twisted pair design aids in reducing crosstalk, ensuring high-speed and error-free data transfer.

Item no. FSP2000

Specification:

- Connector 1: USB 3.1 Type C female
- Connector 2: USB 3.1 Type C female with screw locking
- Gold plated contact, Nickel plated shell
- Nut and Screw type: #4-40 nickel plated
- Hole Pitch: 25 ± 0.5 mm
- Cable Conductor: Tinned Copper
- Wire Gauge: 32AWG
- Outer Diameter: 4.6mm
- Shielding: Aluminum foil, Braiding
- Housing: Injection molding
- Jacket: PVC
- Support up to a 4K@60Hz resolution
- Ultra-Fast Data Transfer/Sync (up to 10 Gbps), also support USB quick charging up to 100W
- Compliance: RoHS, REACH

Order Informaiton:

- FSP2000: USB 3.1 Type C female to female Panel Mount Cable, 0.3m, 32AWG, OD4.6mm