

## Square USB 3.0 A and USB C Car Flush Mount Male to Female Cable



**Item no. FSP4405**

### Description:

FARSINCE High Quality Dual Square USB 3.0 A and USB C Car Flush Mount Male to Female Cable is the perfect solution for expanding USB 3.0 Type-A and USB Type-C ports on the dashboard of cars, trucks, motorcycles, boats, yachts, etc. Easy to install, just use an existing hole or cut a hole in the dash and snap it into the socket. With buckles, easy to snap firm in your car's dashboard. Can use for charge and data transfer.

### Specification:

- Connector 1: USB 3.0 Type-A male, USB 3.0/3.1 Type-C male
- Connector 2: USB 3.0 Type-A female, USB 3.0/3.1 Type-C female
- Gold plated contact, Nickel plated shell
- Cable Conductor: Bare Copper
- Wire Gauge: 28/28/24AWG for USB 3.0 Type-A OD5.5mm; 30/30/24AWG for USB 3.0 Type-C OD4.5mm; 32/32/24 AWG for USB 3.1 Type-C OD4.5mm
- Shielding: Aluminum foil, Braiding
- Housing: Injection mold
- Jacket: PVC
- USB 3.1 Type-C support transfer rate reaches to 10 Gbps, Video resolution up to 4K@60Hz
- Support super speed USB 3.0 devices and the transfer rate reaches to 5Gbps
- Backward compliant with high-speed USB 2.0 (480Mbps), full-speed USB 1.1 (12 Mbps) and low speed USB 1.0 (1.5 Mbps)
- Compliance: RoHS, REACH

### Order Informaiton:

- FSP4405A-010: 1.0m, USB 3.0 A male to female and USB 3.0 C male to female Square Buckle flush Car panel mount Cable, 28/28/24AWG for USB 3.0 Type-A OD5.5mm; 30/30/24AWG for USB 3.0 Type-C OD4.5mm
- FSP4405A-020: 2.0m, USB 3.0 A male to female and USB 3.0 C male to female Square Buckle flush Car panel mount Cable, 28/28/24AWG for USB 3.0 Type-A OD5.5mm; 30/30/24AWG for USB 3.0 Type-C OD4.5mm
- FSP4405B-010: 1.0m, USB 3.0 A male to female and USB 3.1 C male to female Square Buckle flush Car panel mount Cable, 28/28/24AWG for USB 3.0 Type-A OD5.5mm; 32/32/24 AWG for USB 3.1 Type-C OD4.5mm
- FSP4405B-020: 2.0m, USB 3.0 A male to female and USB 3.1 C male to female Square Buckle flush Car panel mount Cable, 28/28/24AWG for USB 3.0 Type-A OD5.5mm; 32/32/24 AWG for USB 3.1 Type-C OD4.5mm